## **P-Grip HEXA / MESH / SQUARE** A slip resistance solution

A high quality structurally rated film faced plywood developed and engineered with added slip resistance. Fully certified to Australian Standard AS 6669. Each with slip resistance classifications (AS 4586-2013). All veneer in the manufacture is certified FSC from sustainable forests.

Bond	Phenol formaldehyde, A-Bond
Timber species	Eucalyptus core, hardwood face / back
Film	250g/m <sup>2</sup> Textured black phenolic resin coating, Reverse smooth125g/m <sup>2</sup>
Formaldehyde emission	Super E0
Edges	Sealed with 2 layer acrylic paint
Slip rating	HEXA: P3 Slip resistance classification (AS 4586-2013)
Finish	MESH: P5 Slip resistance classification (AS 4586-2013)
	SQUARE: P5 Slip resistance classification (AS 4586-2013)
Tolerances	In accordance with AS 6669
Environment	FSC Certified

Thickness	Size (mm)	Stress Grade	Weight / Sheet	Pieces / pack
9 mm	2400 x 1200	F14*	17 kg	100
12 mm	2400 x 1200	F14*	22 kg	75
17 mm	2400 x 1200	F17	30 kg	50
25 mm	2400 x 1200	F17*	45 kg	36

\* Made and tested in accordance with AS 6669.

Looking for prices and more info? Contact our offices below, our team will be happy to assist.

Sydney	02 8805 2300
Melbourne	03 9310 1343
Brisbane	07 3287 4966
Perth	08 9309 8700



General enquiries: panels@peri.com.au



